

A sliding track system designed for mirror and decorative glass panel doors in 2, 3 or 4-door applications. The extruded aluminium mirror door frame includes horizontal rail trims and vertical handle trims with finger grip. It also features rubber bumper inserts for anti-collision and protection for the vertical frame and jamb. All visible extrusions are pre-finished in a durable powdercoat white.

The Mirror Robe system can also be used for 19mm thick timber doors by excluding the mirror framing and fixing the adjustable roller assemblies directly to the rear of the doors.

**FEATURES**

- Track:** Aluminium double top track  
Aluminium double bottom track
- Wheel assembly:** Single-wheel assemblies with height adjustment screw
- Key features:** Screw down bottom track fitting
- Door Guide:** Door top-mounted nylon guide with adjustable anti-lift screw



**TRACK VIEW**



**GUIDE VIEW**



**TECH SPECS**

- Included Feature
- Optional Extra

<b>System Type</b>	Multi-Sliding
<b>Max. Weight Door/Panel</b>	50kg
<b>Door/Panel width (mm)</b>	Up to 900
<b>Door Thickness (mm) min.</b>	19 (timber) 4-6 (mirror)
<b>Track Length (mm)</b>	5000mm
<b>Suits No. of doors</b>	2 to 4
<b>Track Type</b>	Aluminium white finish

External door	
Internal door	
Wardrobe doors	○
Cupboard doors	○
Glass Cabinet doors	
Wall mounted track	
Top mounted track	
Floor fixed track	○
Top hung wheel	
Bottom rolling wheel	○
Door side fix	
End pivoting	
Centre pivoting	
Bottom guide	
Top guide	○
End stop	
Soft-close	
Pelmet	

**MIRROR ROBE COMPONENTS & REPLACEMENT PARTS**

	<b>TT56116:</b> Double Headguide Channel 5000mm White		<b>TT56316:</b> Double Bottom Track 5000mm White
	<b>TT57310:</b> Snap-in Cover Strip 5000mm Charcoal		<b>TT56516:</b> Door Frame Handle 5000mm White
	<b>TT56716:</b> Door Frame Rail 5000mm White		<b>TT56506:</b> Handle Bumper 100m Roll White
	<b>TT90500:</b> Wheel Assembly		<b>TT56600:</b> Nylon Door Guide
	<b>TT79318:</b> Wedge for 4mm mirror 20m Roll Black		

**ARCHITECTURAL DRAWINGS**

