

The Roller Bearing 6 double sliding door system is a versatile glass door system which is slimline in design for maximum visibility yet strong enough to carry 60kg glass panels. Ideal for use in cabinets and vanities as well as small reception windows and display windows.

The Roller Bearing 6 single sliding door system is a great compliment to the double track version. It features all of the same characteristics but in a single track. Ideal for use as a third door or as a stand alone panel for single access requirements. It may also be used for small cavity style windows and access openings.



TRACK VIEW



GUIDE VIEW



TECH SPECS

- Included Feature
- Optional Extra

System Type	Multi-Sliding
Max. Weight Door/Panel	60kg
Door/Panel width (mm)	Up to 2000
Door Thickness (mm) min.	6-6.38
Track Length (mm)	4500mm
Suits No. of doors	2
Track Type	Aluminium - anodised/mill finish

External door	
Internal door	
Wardrobe doors	
Cupboard doors	○
Glass Cabinet doors	○
Wall mounted track	
Top mounted track	
Floor fixed track	○
Top guide	○
End stop	
Soft-close	
Pelmet	
Max Door Size (m²)	3.60
Max Door Height (mm)	1800
Door Width (mm)	Half Opening Width + 25mm (Will give a 50mm overlap)

ROLLER BEARING 6
COMPONENTS & REPLACEMENT PARTS

	TT02111: Aluminium Double Headguide with Pile - 4500mm - Mill		TT02112: Aluminium Double Headguide with Pile - 4500mm - Clear Anod.		TT02311: Aluminium Single Headguide with Pile - 4500mm - Mill
	TT02312: Aluminium Single Headguide with Pile - 4500mm - Clear Anod.		TT02412: Aluminium Head Race - 4500mm - Clear Anod.		TT04606: Nylon End Plate - White
	TT04608: Nylon End Plate - Black		TT04613: Nylon End Plate - Bright Silver		TT04711: Aluminium Double Track - 4500mm - Mill
	TT04712: Aluminium Double Track - 4500mm - Clear Anod.		TT04811: Aluminium Race Section with Pile - 4500mm - Mill		TT04812: Aluminium Race Section with Pile - 4500mm - Clear Anod.
	TT07100: Finger Pull Assembly for 5-6mm Glass		TT08900: Glazing Wedge 40m		TT08910: Glazing Wedge per m
	TT41651: Aluminium Track - 5000mm - Mill		TT50000: Adjustable Sheave (TT500A) - (SS Wheel)		TT50010: Adjustable Sheave (TT500B) - (Nylon Wheel)
	TT41652: Aluminium Track - 5000mm - Clear Anod.				

ARCHITECTURAL DRAWINGS

GLASS PREPARATION DETAILS:

Cowdroy recommends all glass have polished edges and rounded or tipped corners.

