

An ultra-slim sliding cupboard door track, designed for 16mm thick doors. The dual-wheel assembly features a door-fix plate with height adjustment slot for accurate door alignment. The enclosed aluminium track allows for a 20kg door capacity. Install back to back to allow for multiple door applications.



**FEATURES**

- Track:** Enclosed aluminium top track
- Wheel assembly:** Dual-wheel assemblies with door side-fix plate
- Key features:** Ultra-slim design for visual appeal
- Door Guide:** Floor mounted nylon guide - slimline and unobtrusive

**TRACK VIEW**



**GUIDE VIEW**



**TECH SPECS**

- Included Feature
- Optional Extra


<b>System Type</b>	Sliding
<b>Max. Weight Door/Panel</b>	20kg
<b>Door/Panel width (mm)</b>	Up to 650
<b>Door Thickness (mm) min.</b>	16
<b>Track Length (mm)</b>	4900mm
<b>Suits No. of doors</b>	Single/Multiple
<b>Track Type</b>	Aluminium enclosed mill finish

External door	
Internal door	
Wardrobe doors	○
Cupboard doors	○
Glass Cabinet doors	
Wall mounted track	
Top mounted track	○
Floor fixed track	
Top hung wheel	○
Bottom rolling wheel	
Door side fix	○
End pivoting	
Centre pivoting	
Bottom guide	○
Top guide	
End stop	
Soft-close	
Pelmet	

**TUDOR  
COMPONENTS & REPLACEMENT PARTS**



**TT55000:**  
Dual-Wheel Assembly



**TT55241:**  
Aluminium Top Track 4500mm Mill



**TT03000:**  
Nylon Door Guide

**ARCHITECTURAL DRAWINGS**

